














CERTIFICATION AND CLASSIFICATION			Stella
CE certification	EN 14041:2004/AC:2006		2701-0070-DoP-2021-11
Classification	ISO 10874 (EN 685)	 	Commercial: 34 Industrial: 43
TECHNICAL CHARACTERISTICS			Stella
Extreme protection PUR reinforcement			yes
Total thickness	ISO 24346 (EN 428)		2,00 mm
Wear layer thickness	ISO 24340 (EN 429)		0,70 mm
Total weight	ISO 23997 (EN 430)		2,22 kg/m ²
Form of delivery - Rolls	ISO 24341 (EN 426)		25 lm (15-25 lm) x 2 m
Wear layer binder content	ISO 11638		Type 1
TECHNICAL PERFORMANCES			Stella
Dimensional stability	ISO 23999 (EN 434)		Requirement by standard: < 0,4 % Tarkett result: ≤ 10,021 %
Reaction to fire	EN 13501-1		Bfl - s1
Residual indentation	ISO 24343-1 (EN 433)		≤ 0,10 mm
Impact sound reduction	ISO 717/2		10 dB
Underfloor heating			Suitable provided that the surface of the subfloor does not exceed 27°C
Fungi and bacteria resistance	EN ISO 846/2019		Does not contribute to infection spreading
Slip resistance / Ramp test	DIN 51130		R 10
Castor chair test	ISO 4918 (EN 425)		Excellent
Furniture leg	EN 424		Pass
Light fastness	ISO 105 B02 - Method 3		≥ 6
Thermal resistance	EN 12524		0,01 - 0,02 m ² K/W
Static electrical propensity	EN 1815		≤ 2 kV (antistatic)



 2701-0070-DoP-2021-11	 This product is 100% recyclable	 EN 13893	 EN 1815	Manufactured by: Tarkett d.o.o. Bačka Palanka Industrijska zona 14 21400 Bačka Palanka SERBIA
--	--	---	--	---