

QUALITY
 ORDER CODE

WIDTH (±) cm
 TYPE
 GAUGE AND TYPE
 TEXTURING
 DYEING/PRINT METHOD

PILE COMPOSITION
 FIBRE BRAND
 MOTHPROOF

PRIMARY BACKING
 SECONDARY BACKING

PILE WEIGHT (±) gr/m²
 TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
 TOTAL HEIGHT (±) mm
 NUMBER OF KNOTS (±) m²
 STITCHES OVER WIDTH (±) / 10 cm
 STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
 REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
 PILE IN/OUT

DATE: 15/11/2019
 REPLACES: 2/09/2019

SOFT DISTINCTION SB
SDI

± 400-500
 COLLECTION
 1/10" CUT PILE

SOLUTION DYED

PP

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 1.760
 ± 2.730

± 10,0
 ± 12,0
 ± 181.240
 ± 39,40
 ± 46,00

±
 ±

± 25
 PILE IN

LANO CLASSIFICATION

BEDROOM ✓
 LIVING ROOM ✓
 OFFICE
 CASTOR ROLLCHAIRS DOMESTIC USE ✓
 CASTOR ROLLCHAIRS PROFESSIONAL USE
 STAIRS DOMESTIC USE ✓
 STAIRS PROFESSIONAL USE
 ELECTROSTATIC BEHAVIOUR
 UNDERFLOOR HEATING
 BATH ROOM
 NON-FRAY
 PERSONAL COMPUTER

PRODIS-NUMBER
 GUT-NUMBER
 DIBT
 UPEC n°
 CLASSIFICATION
 HQE
 EN 1307

✓
 ✓
 ✓
 ✓
 NO SHOCK
 ✓

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
 CLASSIFICATION BS7131

Cl. 23
 Domestic Heavy



LC5



Efl



LOW RADIUS

HEAVY NON-DOMESTIC

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m ² /KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

SOFT DISTINCTION SB

± 25



± 0,15



± 1,5

≤


≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB 400</u>	SDI	<u>SB 500</u>
0042	ANEMONE 2	0042
0212	TOBACCO 2	0212
0242	CREAM 2	0242
0272	ALMOND 2	0272
0432	BAMBOO MAT 2	0432
0462	HEMP 2	0462
0832	ASH 2	0832
0842	MOONSHINE 2	0842
0844	MOONSHINE 4	0844
0852	MOONBEAM 2	0852
0862	GRANITE 2	0862
0872	SILVER 2	0872
0874	SILVER 4	0874
0882	PEARL 2	0882

<u>SB 400</u>	SDI	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(14)

(14)